

Description

The PT124Y-610 rigid rod type melt pressure gauge features diaphragm isolation, on-site pressure pointer indication, a mechanical structure, requires no power supply, uses a genuine German movement, and allows for reversible dial mounting. The case can be adjusted 360 degrees for optimal viewing angle.


Features

- High cost-performance ratio
- Stainless steel encapsulation
- Easy installation
- Good stability and repeatability

Applications

- Chemical fiber equipment
- Plastic and rubber manufacturing equipment
- Polyester, petrochemical, and steam equipment
- Pressure measurement and control of various high-temperature fluids

Dimensions



Parameters

Pressure range	0~5MPa~150MPa
Overload	150%FS
Display mode	Pointer
Pointer accuracy	$\pm 1.6\%FS$; $\pm 2.5\%FS$
Dial diameter	100mm
Internal filling medium	Mercury
Operating temperature	Max 400°C
Rigid stem length	152 ; 200 ; 250 ; 305 ; 350 ; 400mm
Process connection	1/2" -20UNF ; M14*1.5

Installation dimensions diagram

Flat surface seal	D1	M18×1.5	M22×1.5	G3/8"	G3/4"
	D2	Φ10.2	Φ16.1	Φ10.2	Φ18.3
	D3	Φ15.5	Φ20.1	Φ14.5	Φ24.2
	M	Φ19	Φ23	Φ17	Φ28
	A	11	11	9	11
	B	13	13	10	14
	C	40	25	25	40
45° bevel seal	D1	M12×1.5	M14×1.5	1/2-20UNF	M18×1.5
	D2	Φ8.1	Φ8.1	Φ8.1	Φ10.2
	D3	Φ10.8	Φ12.5	Φ11	Φ15.5
	D4	Φ13	Φ15	Φ14	Φ19
	A	6	6	6	6
	B	9	9	9	11
	C	16	16	16	20



CONTACT US

5-6F No.8 Building No.115 ,Lane 1276 Nanle Road,Songjiang District

Shanghai 201600 China

Tel: +86-21-51691919 67755189

Fax: +86-21-67755185

E-mail: info@zhyqsensor.com

Web: www.zhyqsensor.com